



## Submittal Data

**Submittal Data Model No.:**

**Description: Dual Insulated Line Set**

Job Name:

Location:

Date:

Purchaser:

Engineer:

Submitted to:

For:

Review

Approval:

Model number	Description
TCP09L15	15 feet line set – 1/4" liquid & 3/8" suction with 3/8" insulation & flare nuts
TCP09L25	25 feet line set – 1/4" liquid & 3/8" suction with 3/8" insulation & flare nuts
TCP09L50	50 feet line set – 1/4" liquid & 3/8" suction with 3/8" insulation & flare nuts
TCP12/18L15	15 feet line set – 1/4" liquid & 1/2" suction with 3/8" insulation & flare nuts
TCP12/18L25	25 feet line set – 1/4" liquid & 1/2" suction with 3/8" insulation & flare nuts
TCP12/18L50	50 feet line set – 1/4" liquid & 1/2" suction with 3/8" insulation & flare nuts
TCP24L15	15 feet line set – 3/8" liquid & 5/8" suction with 3/8" insulation & flare nuts
TCP24L25	25 feet line set – 3/8" liquid & 5/8" suction with 3/8" insulation & flare nuts
TCP24L50	50 feet line set – 3/8" liquid & 5/8" suction with 3/8" insulation & flare nuts
TCP3/8 & 3/4L25	25 ft line set – 3/8" liquid & 3/4" suction with 3/8" insulation
TCP3/8 & 7/8L25	25 ft line set – 3/8" liquid & 7/8" suction with 3/8" insulation



- Can be installed alongside with all brands of mini-split ductless air conditioner and heat pump.
- All line sets include copper lines with both liquid and suction lines insulated with 3/8" PE thickness white insulation.
- Each set is equipped with flare nuts on both ends.
- Copper tube: ASTM B280.
- Surface burning characteristics: UL 94.
- Meets ASTM E84 for smoke and fire.
- Has an exterior that's resistant against UV.
- Each item is placed in separate box, thus more convenient to be shipped and stored.